

Refrigerated, self-contained

Liquid CO₂ Tanks

Portable

- Self-contained refrigerated tanks store liquid CO₂ – maintain temperature and pressure.
- Mounted on structural steel base for easy installation.
- Available with integrally mounted transfer pump/ flowmeter option.



SPECIFICATIONS

PRESSURE VESSEL: ASME coded for maximum working pressure of 350 psig (24.6 kg/cm²).

PIPING: Schedule 80 black pipe, forged steel fittings, ball type valves.

SAFETIES: ASME approved direct spring loaded or pilot operated, sized for unconfined outdoor installation.

OPTIONAL LIQUID CO₂ TRANSFER PUMP AND FLOWMETER: In varying capacity ranges.

INSULATION: 4" (10.1 cm) Polyurethane.

OUTER JACKET: 0.063" (0.16 cm) aluminum.


LIQUID LEVEL GAUGE: Differential pressure indicator type with 6" (15 cm) dial.

PRESSURE GAUGE: 0 to 600 psi (0 to 42.2 kg/cm²) with 6" (15 cm) dial.

CONTROL CABINET: Prefinished aluminum with lockable access door. Add 4'0" (122 cm) to length shown for fold down door clearance.

Nominal Capacity		Height		Width		Length		Empty Weight	
U.S. Pounds	Kilo-grams	Ft	M	Ft	M	Ft	M	U.S. Pounds	Kilo-grams
12,000	5,443	8'3"	2.51	15'0"	4.57	6'2"	1.88	10,000	4,536
28,000	12,700	8'10"	2.69	18'9"	5.72	7'8"	2.34	15,500	7,031

The Wittmann Company, LLC



1 Industry Drive Suite A
Palm Coast, Florida USA
32137

Phone: +1.386.445.4200
Fax: +1.386.445.7042
E-mail: co2@wittmann.com